

Swissphone RE729

The latest analog receiver for Emergency Professionals

Narrowband-Ready



The most important performance features

- > 32 addresses with 50 user profiles
- > Frequency synthesizing via PLL reduces set-up times for deployment
- > Four minutes voice memory, dividable, can be set as fixed or dynamic (stored voice)
- > IP54 certified (splash proof)
- > Optional multi channel, allows the pager to utilize several different receiving frequencies
- > Scan capability on all channels

))) Designed for **Emergency Professionals**, the RE729 can be programmed with the five nationwide VHF VTAC and VCALL channels (**151.1375, 154.4525, 155.7525, 158.7375** and **159.4725MHz**). Up to 45 additional channels may be programmed by the user. Together with the flexible scan feature and the class leading configurability the RE729 is ideal for day to day use.

))) Thanks to its user profiles, the RE729 can be adapted at any time to fit changing assignments. The time stamp and alert timer provide additional support for scheduling a response. The RE729 is the ideal 2- and 5-Tone pager for use in all alerting and emergency dispatching networks.

))) The legendary swiss quality, throughout construction highlight the functionality and durability of Europes most popular pager. Whether you are an Emergency Professional or a Voluntary Fireman Swissphone analog pager are unquestionably your best choice.



RE729 stored voice

32 addresses in 50 user profiles: 50 user profiles and the easy-to-activate expansion profile provide a wide range of options to configure the 32 addresses to the requirements of the task at hand and can be assigned appropriately.

Improved display legibility: The 4-digit, 7-segment display constantly shows the currently active profile. The time is displayed at the touch of a button. If the RE729 receives an alert, the receiving address appears first, then the stopwatch flashes. When the message is retrieved, the alert time is also shown.

Economical: Thanks to PLL (phase-locked loop) technology, the receiving frequency can be pre programmed, in addition to the operating functions.

Reliable and robust: Made in Switzerland for a persuasive combination of quality and functionality. State-of-the-art technology, excellent reception and its handy format make the RE729 the best in its class. The Swissphone compact casing is exceptionally robust thanks to its two interlocking convex halves and further protection is provided by all-round rubber cushioning.

Safe investment: The world-wide service net of Swissphone assures an optimal and continuous functionality of the devices. Replacement parts are kept available for at least seven years after production of a device ceases.

Performance features	RE729 stored voice
Memory for voice messages	4 minutes, can be divided, dynamic and fixed
VHF Frequency bands (MHz)	RE729: 151 - 160 MHz RE629: 146-155 MHz / 155-164 Mhz / 164-174 MHz
UHF Frequency bands (MHz)	RE629: 450-470 MHz
Frequency programming range	RE729: 9 MHz (151-160 MHz) RE629: 1MHz
Channel spacing	12.5 / 20/25 kHz (narrowband-ready)
Frequency processing	PLL
Sensitivity (best position) 4m/2m	< 3,5 µV/m
Option Multi-Channel, scannable	yes
Compliance/Norms	EN 300-296-1/300-341-1 // IEC 60068-2-27 (shock) IEC 60069-2-6 (vibration) IEC 60529: 1991+A1:2000 (IP54) // IEC 600068-2-32 (drop test) (Dust: Equally to MIL-STD 810F Method 506.4, Procedure III) (Rain: Equally to MIL-STD 810F Method 510.4, Procedure III)
Sets of tones	32
Frequencies	Single Channel:1 Multi Channel: 50
Alert memory	24
Alarm timer	yes
Vibrator	yes
Clock and alarm display	yes
Monitoring function	yes
Standard battery type, AA size	yes
Power management	dry cell (1.5V) 165 h NiMH rechargeable (2200 mAh) 180 h NiCd rechargeable (800 mAh) 65 h
Case (H x W x D)	78 x 53 x 24 mm // 3.1 x 2.1 x 0.95 inches
Protective case category	IP54 (EN 60529, category 2)

Specifications subject to change

-))) Push to Listen
-))) Silent Alert with or without Voice Announcement
-))) Manual Reset, Timeout Reset
-))) Swissphone Smart Reset

Swissphone llc
1194 Ash Street, Suite C
Windsor, CO 80550
(800)-596-1914
www.swissphonena.com

